

WARNING!

DB75/75V/75VS Heads

Machine operators and others in the work area should always wear safety glasses to prevent serious eye injury from fasteners and flying debris when loading, operating, or unloading the stitcher machine.

Do not operate this stitcher head without all stitcher machine guards in place. Do not modify the guards in any way. Always disconnect the power supply before removing any guards for servicing.


Never operate the machine with wire feeding through the head unless there is stock above the clinchers, otherwise serious damage may result.

Always turn power off when making adjustments. Always disconnect the power cord before any disassembly work.

EYEWEAR



REQUIRED



THANK YOU FOR CHOOSING THE DB75, DB75V, OR
DB75VS STITCHER HEAD
FOR YOUR BINDING NEEDS

Table of Contents

Introduction	4
Specifications.....	5
Installation	6
Pre-Inspection	6
Inspection	6
Mounting	6
Assembly	6-8
Operation	9
Wire Threading	9-10
Wire Straightening	11
Adjustments and Settings	12-14
Maintenance.....	14
Lubrication	14-15
Ordering Spare Parts	16
Troubleshooting.....	17-18
Appendices	19
Exploded Drawings.....	19-36
Notes	37
Part Number/Description Cross Reference Index.....	38-39
Registration Card	40
Wear/Replacement Parts.....	41
Warranty	42

Introduction

The DeLuxe Stitcher Müller-Martini Replacement Heads, along with a complete line of fully interchangeable replacement parts are available for current Müller-Martini users. Anywhere the HK75, HK75V and HK75VS are utilized the DeLuxe Stitcher DB75HD, DB75VHD, & DB75VSHD can be used.

The DB75HD has a stitching capacity from 2 sheets up to 5mm (.197”) and will accommodate wire sizes from 20-28 gauge round as well as 21 x 25 and 20 x 24 flat. The perfect replacement head for Müller-Martini Stitchers 221, 235, 321, 335, Prima, Bravo and more, the DB75HD is completely interchangeable.

The DB75VHD & DB75VSHD have a stitching capacity from 2 sheets up to 6mm (.236) and will accommodate wire sizes from 20-28 gauge round as well as 21 x 25 and 20 x 24 flat. This replacement head for Müller-Martini™ Stitchers 301, Tempo, Optima, Supra and the like, is also completely interchangeable.

Each of these heads weighs 7 lbs (3.2 kgs.) independently. The packaged shipping weight including the Wire Guide Spring, Clincher Plate assembly and user manuals is 10 lbs. (4.5 kgs.).

Always use a high quality Galvanized Wire so the plating does not peel. Excessive peeling will cause clogging and the premature wear of many components. Use the following chart as a guide for wire gauge usage.

2 sheets - 1/8” (3mm)	25 gauge
1/8” (3mm) - 7/32” (6mm)	23 or 24 gauge
For heavy paper	20 to 22 gauge round or 20x24 flat

NOTE: ALL PRODUCTS ARE MANUFACTURED BY DELUXE STITCHER.

Specifications

Weight: Shipping Weight 10 lbs (4.5 kg)
 Box Dimensions 21" x 10" x 7" (53 x 25 x 18 cm)
 Stitcher Head:
 DB75HD 7 lbs (3.2 kg)
 DB75VHD 7 lbs (3.2 kg)
 DB75VSHD 7 lbs. (3.2 kg)

Physical Dimensions

Height 8.5" (22 cm)
 Width 3.5" (9 cm)
 Depth 4.25" (11 cm)

Stitching Capacity

DB75HD Two Sheets to 13/64" (5 mm)*
 DB75VHD Two Sheets to 1/4" (6 mm)*
 DB75VSHD Two Sheets to 1/4" (6mm)*

Wire Types

. 20 through 28 round or
 21 x 25 and 20 x 24 flat

* Actual stitching thickness capacity depends on the type of stock being stitched and the capacity of the saddle stitcher being used.

Stitcher Head / Stitcher Machine Compatibility					
Stitcher Machine	Compatible Stitcher Heads				
JGV	DB75HD	DB75VHD	DB45HD	Loop not recommended.	⊘
Fox, 221, 235	DB75HD	DB75VHD	DB45HD	DB75VHD-LOOP	⊘
331, 335	DB75HD	DB75VHD	DB45HD	DB75VHD-LOOP	⊘
Bravo/Prima (Built before 2004)	DB75HD	DB75VHD	DB45HD	DB75VHD-LOOP	⊘
Bravo/Prima (Built 2004 or later)	DB75LPHD	DB75VLPHD	DB45LPHD	DB75VLPHD-LOOP	⊘
Valore/Presto (All)	DB75MPHD	DB75VMPHD	DB45MPHD	⊘	⊘
1509/Minuteman (Built before 2004)	DB75MMHD	DB75VMMHD	DB45MMHD	DB75VMMHD-LOOP	⊘
1509/Minuteman (Built 2004 or later)	DB75MMMPHD	DB75VMMMPHD	DB45MMMPHD	DB75VMMMPHD-LOOP	⊘
301/Optima/ Tempo/Supra	⊘	⊘	⊘	⊘	DB75VSHD

Installation

Pre-Inspection

Carefully inspect the condition of the shipping container before unpacking your replacement Head for Müller-Martini Stitchers. If the container is broken or damaged and there is evidence that the

stitcher head may be damaged, immediately notify the carrier who delivered the head and the DeLuxe Stitcher Graphic Arts Representative from whom the Head was purchased.




Figure 1 - Inspection

Inspection (Figure 1)

As you carefully unpack the replacement head, check to make sure all components were delivered and are in good working order. Use **Figure 1** in this manual for reference to the following pieces:

- Replacement Head for Müller Martini Stitchers: DB75HD, DB75VHD or DB75VSHD
- Wire Guide Spring [070286]
- Clincher Plate Assembly [077030 or 077030C]
- Feed Release Handle [070119]
- 2.5, 3, 4 and 5 mm Hex Key Wrenches [G20361, G20360, G20373 and G20362]
- Stitch samples

Mounting & Assembly (Figure 2-6)

Attaching the Feed Release Handle (Figure 2)

From out of the box, secure the Feed Release Handle [070119] to the Stitcher Head by slipping the Handle over the Feed Release Cam Assembly [070118] and securing it with the provided screw, inserting it through the Spring. Make sure the Handle is angled toward the outside of the Head when you the screw is tightened.




Figure 2- Feed Release Handle




Figure 3a - Mounting the Head






Figure 3b - Mounting Variation for DB75VS

Mounting the Head (See Figure 3)

Attaching the Wire Guide Spring (Figure 4)


Mounting the Clincher Plate (Figure 5 & 6)

Figure 5 - Mounting Clincher Plate Assembly



! CAUTION


Always disconnect the power before assembling or making adjustments to your stitcher machine.



Operation

Wire Threading (Figure 7-8)


Figure 7 - Wire Threading



Before the Stitcher Machine is turned on, release the Wire Holder Assembly [070135A] (*Not shown- See Fig. #*) secured by the Wire Holder Retaining Spring [070183 or 070583] by loosening the Screw [072004] on the front of the Head. Thread the wire from the Spool under the studs on the Wire Guide Spring (070286), between the Wire Oiler Felts [G20293] on the Spring and into the Wire Nozzle [070181]. Turn the Feed Release Handle [070119] clockwise so that the Small Feed Gear [070112] is disengaged from the Large Feed Gear [070510A].

Continue to push wire through the Replacement Head until the end of the wire passes the Small and Large Feed Gears, enters the Wire Tube [070544] and begins to come out the bottom of the Wire Tube. Then using a small screw driver, wedge the wire up until it enters the Fixed Wire Cutter [070600C]. Engage the Small and Large Feed Gears by turning the Adjustable Lever counter-clockwise.

Note: It will take two full cycles for the proper length staple to come out of the Head.



Wire Straightening (Figure 9)

Once threaded, cycle the Stitcher Machine and watch the wire feeding out of the the Cutter Box [070197A or 070597A] to the right of the Moving Cutter [070145C]. The wire should be traveling in an approximate horizontal direction when exiting the Cutter Box.

Top-to-Bottom Adjustment

If the Wire is feeding in an upward or downward direction, the Wire Straightener [070206A] will have to be adjusted. Loosen the Screw [G20589] securing the Wire Straightener to the Cutter Box. If the wire is feeding in an upward direction, slide the Wire Straightener down slightly. Conversely, if the wire is feeding in a downward direction, slide the Assembly up slightly.

Make sure to tighten the Screw after every adjustment to see accurate results. Allow enough Wire to be fed through the Head so that an accurate assessment can be made. Make sure the ends of each cut piece of Wire is free of burrs, which would negatively affect the driving and clinching of the formed Wire.




Figure 9 - Wire Straightening

! WARNING

Make sure the Wire Holder Assembly has been removed before tripping the Machine to avoid jams and the chipping of parts.

Adjusting the Length of the Right Leg (Figure 10-12)

Setting the Stitch's Right Leg (& Setting It's Center)

If after a few stitches, the length of the stitch's right leg is too short or too long, you will need to make adjustments. Adjustments are always made to the right leg to compensate for the length of the left leg. First adjust the stitch's right leg to match the left and then make adjustments for the overall length of the stitch or wire draw.

Power off the Stitcher Machine and release the Extension Spring [074002] from the Feed Gear Operating Lever Pin [043002] on the Replacement Head. Disengage the Small Feed Gear from the Large Feed Gear by turning the Feed Release Handle [070119]. Push the Feed Gear Operating Lever [077001] down which will move the pin on the Feed Gear Pinion [070111A] out of the way of the Feed Gear Stop [077026]. Loosen, but do not remove, the Screw [G20589] securing the Feed Gear Stop to the top of the Cutter Box Assembly. If the legs of the stitch are not even, do one of the following:

If the right leg is too short, slide the Feed Gear Stop to the left slightly, to lengthen it.

If the right leg is too long, then adjust the Feed Gear Stop slightly to the right.

Tighten the screw and replace the Extension Spring.




Figure 10 - Adjusting the Right Leg





Figure 11 - Adjusting the Right Leg

! CAUTION

Always disconnect the power before assembling or making adjustments to your stitcher machine.

Power on the Stitcher Machine and jog the Stitcher to observe the length of the stitch's right leg after the initial adjustment. Continue to make adjustments and re-test the Head until the length of the stitch's right leg is satisfactory.

When set, any one of the above stitches are regarded as good stitches with the two on the left needing the next step in adjustment and the two on the right as properly set (with amount of gap a matter of preference).




Adjusting the Stitch Gap or Wire Draw (Figure 13)

Adjusting the Overall Length of the Stitch (Adjusting the Stitch Gap)

To change the overall length of the stitch, or more specifically to change the gap between the legs of the stitch, the position of the Cutter Box must be adjusted. Begin by releasing the Extension Spring from the Feed Gear Operating Lever Pin. Disengage the Small Feed Gear and the Large Feed Gear by turning the Feed Release Handle. Push the Feed Gear Operating Lever down which will move the pin on the Feed Gear Pinion Pin out of the way of the Feed Gear Stop. Loosen the Screw [072006] securing the Cutter Box to the Stitcher Head.


If the legs are too short, increase the overall length of the stitch's legs by sliding the Cutter Box to the left and if too long, to the right. Tighten the Screw, attach the Extension Spring and power on the Stitcher Machine. Trip the Stitcher to observe the overall length of the each stitch after the initial adjustment. Repeat as necessary.



Adjusting the Clincher Points (Figure 14)

If the clinch on the staple is not tight enough, the Clincher Points [077015] have to be raised. Conversely, if the clinch is too tight, the Clincher Points have to be lowered. This adjustment is made on the Stitcher Machine and so cannot be completely explained in this manual as each individual Machine is different.

The final position of the Clincher Points should be flush (or slightly above flush) with the Clincher Plates. The best way to see the position of the Clincher Points is to jog the Machine where the Driver is at the lowest position of its stroke, the Clincher Points are at their highest position. Jog the Stitcher Machine until the Stitcher Head is just past this point to reveal the Clincher Points' position. To be sure that the Points are at the best position possible, run a few test stitches and compare the clinched staples.




! CAUTION

Always disconnect the power before assembling or making adjustments to your stitcher machine.

Maintenance

Lubrication (Figure 15)

Use any standard S.A.E. #10 oil for lubricating the heads. Heads that are in constant operation should be lubricated daily. Heads that are operated periodically should be lubricated every five pound wire spool change or every month, whichever ever comes first. Usually, only a drop of oil is required at each lubrication point. Care must be taken that those parts of the head that contact the work to be stitched are free of oil. Lubricate regularly instead of excessively. Excessive oiling will result in work becoming spotted with oil. Use one drop of oil in the following lubrication points:



1. At the top of the Bonnet [070000 or 070500] on either side of the Driver Slide [070551A or 070151A] and Bender Slide [070162A or 070562A].

2. In the hole of the Feed Cam Plunger Bushing [077010].

3. On the shaft of the Feed Release Cam Assy. [070118] in the front of the Small Feed Gear [070112]


4. The oil hole in the front of the Bonnet [070000 or 070500] - this lubricates the Clutch Bearing located inside the Feed Gears

5. On the Cutter Operating Lever

[070230] behind the Cutter Box [070197A or 070597A].

6. In between the Wire Holder Retaining Spring [070183 or 070583] and the Wire Holder [070135A] and on the Hook Pivot Pin [073009] in the Wire Holder [070135A]

7. On each of the Clincher Point Pivot Pins [077018-2] on the Clincher Back Plate [077018]



Ordering Spare Parts

Feed Gear Information (Figure 16)

Correct clutch assembly.





Figure 16 - Feed Gear Pinion Assy

Always disconnect the power cord before any maintenance is done or adjustments are made to the Müller Replacement Head

! CAUTION



In time, you will need to replace some parts in your G5 style Stitcher Head. When this happens, first locate the needed part in one of the following diagrams. Then locate the DeLuxe Stitcher part number and contact your Graphic Arts Representative to order the part by the part number, description and quantity. Customer Service Hotline: 800-634-0810


solving your wire stitching needs for 125 years...



Troubleshooting (Figure 17)

The quality and quantity of work that can be produced with the Müller Replacement Head is dependent upon the operator making all adjustments as accurately as possible and carefully maintaining the head. The cause of staple imperfections usually can be traced to inaccurate settings or normal wear of moving parts. In the event of trouble of this nature occurring, the operator can, by referring to the following troubleshooting chart, quickly locate and remedy the cause or causes of the trouble.

The following is a brief list of problems and solutions which should cover the majority of situations encountered when stitching with the DB style Stitching Heads.



PROBLEM: Right Leg Short

SOLUTION: Move the Feed Gear Stop to the right, slightly.
(See page 11)

PROBLEM: Right leg Long

SOLUTION: Move the Feed Gear Stop to the left, slightly.
(See page 11)

PROBLEM: Corner Buckled

SOLUTION: Check the Driver for a chipped corner and rotate or replace it if needed. Use a heavier gauge wire.

PROBLEM: Leg(s) Buckled

SOLUTION: Check the Wire Cutters and Wire Cutter Operating Slide for wear and rotate or replace if needed. Use a heavier gauge wire.

PROBLEM: Crown Buckled

SOLUTION: Check Supporter Spring tension on the Head. If it is too loose replace it.

PROBLEM: Stitch in Pieces

SOLUTION: Clean and lubricate the Head. Check for hard or brittle wire and replace. Check the tension of the Wire Holder Spring and replace Spring if too loose. Look for wear in Wire Holder pivot point in Bonnet.

PROBLEM: Loose Clinch

SOLUTION: Raise the Clincher Points. (See page 13)

PROBLEM: Legs are Spread or Contracted

SOLUTION: Make sure the wire is feeding straight through the Head. (See page 10) Check the Wire Cutters for wear and rotate or replace if needed. Check the Formers for wear in the grooves and replace if needed.

PROBLEM: Wire jam near Feed Gear

SOLUTION: Tighten Cutters. Check for the following worn parts and replace if necessary. Fixed Cutter, Moving Cutter, Cutter Operating Slide, Cutter Operating Lever, Bender Slide Insert, Wire Guide, Hook, Hook Pivot Pin and Feed Gear Friction Strip.





Figure 17 - Troubleshooting

Bonnet and Wire Guide Spring Sub-Assemblies DB75




SHADED PART NUMBERS DENOTES WEAR PARTS

Bonnet and Wire Guide Spring

Sub-Assemblies; DB75

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
070000	0881.0004.1	Bonnet - DB75
070112	0881.0003.4	Feed Gear, Small
070114	0881.0008.4	Feed Gear Shaft
070118	0881.0018.4	Feed Release Cam Assembly
070119	0022.0270	Feed Release Handle
070144	0881.0042.4	Wire Tube
070181	0881.0009.4	Upper Wire Tube
070183	0034.6302	Wire Holder Retaining Spring
070186	0034.6301	Friction Strip
070230	0881.0006.4	Cutter Operating Lever
070244	0881.0043.4	Wire Tube Clamp
070286	0881.0301.3	Wire Guide Spring
G20520		Lock Washer, M6
071004	0031.5103	Lock Washer, Ribbed, M3
071005	0031.5104	Lock Washer Ribbed, M4
071006	0031.5105	Lock Washer, Ribbed, M5
072004	0030.0048	Screw M6x1.0x12
072009	0030.3434	Screw M3x.5x10
072013	0030.9001	Screw M6x1.0x22
072017	0881.0041.4	Screw M5x0.8x5.5
073002	0031.0759	E-Ring
073005	0031.6310	Spring Pin, M3x10
073006	0031.6312	Spring Pin, M3x12
073007	0031.6316	Spring Pin, M3x16
073010	0881.0030.4	Dowel Pin, M6x32
074004	0034.2370	Compression Spring
077009	0881.0032.4	Feed Cam Plunger
077010	0881.0035.4	Feed Cam Plunger Bushing
077006B	0881.0021.4	Mounting Strap
078008	0023.0957	8mm Shim Washer
078112A		Small Feed Gear Assembly
G20195		Screw M6x1x8
G20287		Wire Oiler Felt Spring
G20292		Wire Oil Felt Washer
G20293		Wire Oiler Felt, 1-1/4 Dia.
G20297		Screw M6x1x40
G20298		Nylock Lock Nut M6x1
G20589		Screw M4x0.7x10

Bonnet and Wire Guide Spring Sub-Assemblies DB75V & DB75VS




SHADED PART NUMBERS DENOTES WEAR PARTS

Bonnet and Wire Guide Spring Sub-Assemblies; DB75V & DB75VS

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
070286	0881.0301.3	Wire Guide Spring
044002	0354.1041.4	Feed Cam Compression Spring
070112	0881.0003.4	Feed Gear, Small
070118	0881.0018.4	Feed Release Cam Assembly
070119	0022.0270	Feed Release Handle
070181	0881.0009.4	Upper Wire Tube
070230	0881.0006.4	Cutter Operating Lever
070244	0881.0043.4	Wire Tube Clamp
070544	0249.1014.4	Lower Wire Tube
071004	0031.5103	Lock Washer, Ribbed, M3
071006	0031.5105	Lock Washer, Ribbed, M5
072009	0030.3434	Screw M3x.5x10
072013	0030.9001	Screw M6x1.0x22
072017	0881.0041.4	Screw M5x0.8x5.5
073002	0031.0759	E-Ring
073006	0031.6312	Spring Pin, M3x12
073010	0881.0030.4	Dowel Pin, M6x32
074004	0034.2370	Compression Spring
077009	0881.0032.4	Feed Cam Plunger
077010	0881.0035.4	Feed Cam Plunger Bushing
078010	0881.4024.4	Feed Cam Plunger Bushing
077027B	0881.0325.4	Mounting Strap, DB75V
078008	0023.0957	Shim Washer, DB75VS
078112A	0881.0364.4	Small Feed Gear, DB75VS
078118A	0881.0363.3	Feed Release Cam Shaft Assembly
078230C	0881.0370.4	Cutter Operating Lever-Carbide
G20195		Screw M6x1x8
G20287		Wire Oiler Felt Spring
G20292		Wire Oil Felt Washer
G20293		Wire Oiler Felt, 1-1/4 Dia.
G20297		Screw M6x1x40
G20298		Hex Nut M6x1

Bonnet and Supporter Sub-Assemblies DB75V & DB75VS

070186
(DB75VS requires the
addition of plastic liner
Part # OSK137-3.
See Page 20.)




SHADED PART NUMBERS DENOTES WEAR PARTS

Bonnet and Supporter Sub-Assemblies; DB75V & DB75VS

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
070114	0881.0008.4	Feed Gear Shaft
070186	0034.6301	Friction Strip
070344	0881.0313.4	Supporter Spring
070500	0881.0300.2	Bonnet - DB75V
070554	0881.0312.4	Supporter
070583	0881.0321.4	Wire Holder Retaining Spring
071005	0031.5104	Lock Washer Ribbed, M4
072004	0030.0048	Screw M6x1.0x12
072005	0030.0051	Screw M6x1.0x25
072010	0030.3447	Screw M4x0.7x5
073005	0031.6310	Spring Pin, M3x10
073012	0881.0314.4	Dowel Pin, M6x55
077021	0881.0311.4	Supporter Holder
077025	0881.0320.4	Wire Holder Guide
G20195	0030.1725	Screw M6x1x8
G20520	0031.0557	Lock Washer Ribbed, M6
G20589	0030.0017	Screw M4x0.7x10, Nylon


Driver and Bender Inserts DB75



Driver and Bender Inserts; DB75

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
071002	0023.0931	Shim Washer
071005	0031.5104	Lock Washer Ribbed, M4
072007	0030.1711	Screw M5x0.8x4
072010	0030.3447	Screw M4x0.7x5
072016	0881.0039.4	Screw M4x0.7x17
073003	0031.5021	Cotter Pin
073008	0031.9106	Rivet
074003	0034.2152	Center Guide Spring
077002	0881.0013.4	Centering Guide Post
077003	0881.0017.4	Centering Guide
077004	0881.0019.4	Driver Slide Shaft
077007	0881.0022.4	Set Collar
077011	0881.0037.4, 0881.0037.3	Hook Guide, DB75
077012	0881.0040.4	Bender Slide Insert
070151A	0881.0051.4	Driver Slide Assembly
070152-20	0881.0153.4	Driver 1.0 Wire
070152-23	0211.0039.3	Driver 0.8 Wire
070152-25	0881.0014.3	Driver 0.6 Wire
070162A	0881.0050.4	Bender Slide Assembly
070548L-20	0881.0152.4	Former LH 1.0 Wire
070548L-23	0881.0184.4	Former LH 0.8 Wire
070548L-25	0881.0016.4	Former LH 0.6 Wire
070550R-20	0881.0151.4	Former RH 1.0 Wire
070550R-23	0881.0185.4	Former RH 0.8 Wire
070550R-25	0881.0014.3	Driver 0.6 Wire
071005	0031.5104	Lock Washer Ribbed, M4
072011	0030.3451	Screw M4x0.7x12
072018	0881.0045.4	Screw M4x0.7x6, Nylon


Driver and Bender Inserts DB75V



Driver and Bender Inserts; DB75V

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
071002	0023.0931	Shim Washer
071005	0031.5104	Lock Washer Ribbed, M4
072010	0030.3447	Screw M4x0.7x5
072011	0030.3451	Screw M4x0.7x12
072015	0249.1054.4	Driver Retaining Screw
072019	0881.0318.4	Allen Head Screw
073003	0031.5021	Cotter Pin
074003	0034.2152	Center Guide Spring
077004	0881.0019.4	Driver Slide Shaft
077007	0881.0022.4	Set Collar
077012	0881.0040.4	Bender Slide Insert
077022	0881.0315.4	Centering Guide, Wide
077023	0881.0316.4	Centering Guide, Narrow
077024	0881.0317.4	Hook Guide, DB75V
070548L-20	0881.0152.4	Former LH 1.0 Wire
070548L-23	0881.0184.4	Former LH 0.8 Wire
070548L-25	0881.0016.4	Former LH 0.6 Wire
070550R-20	0881.0151.4	Former RH 1.0 Wire
070550R-23	0881.0185.4	Former RH 0.8 Wire
070550R-25	0881.0015.4	Former RH 0.6 Wire
070551A	0249.1065.4	Driver Slide Assembly
070552-20	0881.0319.3	Driver 1.0 Wire
070552-23	0881.0367.3	Driver 0.8 Wire
070552-25	0881.0326.3	Driver 0.6 Wire
070562A	0881.0309.4	Bender Slide Assembly
070648R-20	0881.0160.4	Former RH 1.0 Wire
070648R-23	0881.0187.4	Former RH 0.8 Wire
070648R-25	0881.0156.4	Former RH 0.6 Wire
070650L-20	0881.0161.4	Former LH 1.0 Wire, 15mm Crown
070650L-23	0881.0186.4	Former LH 0.8 Wire, 15mm Crown
070650L-25	0881.0155.4	Former LH 0.6 Wire, 15mm Crown
070656-20	0881.0511.3	Driver 1.0 Wire-15mm Crown
070656-23	0881.0331.3	Driver 0.8 Wire-15mm Crown
070656-25	0881.0510.3	Driver 0.6 Wire-15mm Crown


Driver and Bender Inserts DB75VS



Driver and Bender Inserts; DB75VS

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
071002	0023.0931	Shim Washer
071005	0031.5104	Lock Washer Ribbed, M4
072015	0249.1054.4	Driver Retaining Screw, Nylon
072019	0881.0318.4	Allen Head Screw
073003	0031.5021	Cotter Pin
074003	0034.2152	Center Guide Spring
077022	0881.0315.4	Centering Guide, Wide
077023	0881.0316.4	Centering Guide, Narrow
078001	0881.0374.4	Bearing, Mount Shaft, DB75VS
078002	0038.1243	Slide Bearing, DB75VS
078006	0023.0955	Shim, DB75VS
078024	0881.4045.3	Hook Guide, DB75VS
070548L-20 (1.0 mm)	0881.0152.4	Former LH 1.0 Wire
070548L-23 (0.8 mm)	0881.0184.4	Former LH 0.8 Wire
070548L-25 (0.6 mm)	0881.0016.4	Former LH 0.6 Wire
070550R-20 (1.0 mm)	0881.0151.4	Former RH 1.0 Wire
070550R-23 (0.8 mm)	0881.0185.4	Former RH 0.8 Wire
070550R-25 (0.6 mm)	0881.0015.4	Former RH 0.6 Wire
070552-20 (1.0 mm)	0881.0319.3	Driver 1.0 Wire
070552-23 (0.8 mm)	0881.0367.3	Driver 0.8 Wire
070552-25 (0.6 mm)	0881.0326.3	Driver 0.6 Wire
072011	0030.3451	Screw M4x0.7x12
078005	0209.2367.4	Bearing Slide Washer, DB75VS
078012C	0881.0371.4	Bender Insert-Carbide, DB75VS
078551A	0881.0336.3	Driver Slide Assembly, DB75VS
078562A	0354.1036.3	Bender Slide Assembly, DB75VS
G20298		Nylock Lock Nut M6x1


Cutter Box Assembly



Cutter Box Assembly

DELUXE PART NUMBER	MÜLLER™ PART NUMBER CROSS REFERENCE	PART DESCRIPTION
070197A	0881.0010.4	Cutter Box Assembly
070597A	0881.0322.4	Cutter Box Assembly
070210	0034.2252	Cutter Box Spring
070198	0881.0007.4	Cutter Operating Slide
077026	0881.0324.4	Feed Gear Stop
070600C	0881.0198.4	Fixed Cutter - Carbide
070600CS	0881.0505.4	Fixed Cutter - Carbide-Short
071005	0031.5104	Lock Washer Ribbed, M4
071005	0031.5104	Lock Washer Ribbed, M4
070145C	0881.0197.4, 0305.2127.4	Moving Cutter - Carbide
G20520		Ribbed Lock Washer, M6
G20589	0030.0017	Screw M4x0.7x10, Nylon
G20589	0030.0017	Screw M4x0.7x10
072014	0030.9016	Screw M4x0.7x12 LH
071008	0881.0323.4	Washer
072006	0030.0052	Screw M6x1.0x30
G20229	0030.1727	Screw M6x1x12, Nylon
073004	0031.6039	Spring Pin, M5x12
070206A	0249.1074.4	Wire Straightener Assembly

Feed Gear Assembly - DB75, DB75V & DB75VS



USE REPLACEMENT KIT MMKFG1 FOR DB75 AND HK75.

USE REPLACEMENT KIT MMKFG2 FOR DB75V, DB75VS, HK75V, AND HK75VS.

0881.0304.4 (DB75V) or 0881.0368.4 (DB75)

Used together replaces 0881.0308.3


0881.0330.4

Feed Gear Assembly - DB75, DB75V & DB75VS

DELUXE PART NUMBER	MÜLLER PART NUMBER CROSS REFERENCE	PART DESCRIPTION
043002	0031.6491	Grooved Pin
070537*	N/A	Feed Gear Clutch
073001	0031.0757	E-Ring
074002	0034.0302	Extension Spring
077001	0881.0011.4	Feed Gear Operating Lever Assy
070510A*	N/A	Feed Gear, Large
070111A*	N/A	
070511A*		Pinion

* Indicates parts that are not interchangeable with Müller-Martini parts.
All parts used together can be used interchangeably with the HK75 or HK75V.

Wire Holder Assemblies; DB75 & DB75V



Wire Holder Assembly

DELUXE PART NUMBER	MÜLLER PART NUMBER CROSS REFERENCE	PART DESCRIPTION
070135	0881.0031.3	Head Wire Holder
072008	0030.3429	Screw M3x0.5x3
073009	0031.0757	E-Ring
074001	0034.0102	Extension Spring
077013		Wire Hook
070559		DB Head Wire Holder
073009		Hook Pivot Pin
070013		Wire Holder Hook Assembly, VS
072008	0030.3429	Screw M3x0.5x3
074001	0034.0102	Extension Spring


SHADED PART NUMBERS DENOTES WEAR PARTS

Clincher Plate Assemblies

*(When using solid clincher plates remove moveable slide & points.)


SHADED PART NUMBERS DENOTES WEAR PARTS

077030 or 077030C (Carbide)
Replaces 0881.9050 and 0881.8331.3




Standard Clincher Plate

070830A
Replaces 0881.8334.3



Used on Bravo/Prima machines
After 2004, used on all Optima & Supra machines

070850A
Replaces 1550.0023



Used on all Presto & Valore machines
Used on Minuteman (1509) machines built after Jan. 2004

Clincher Plate Assemblies

077030 (0881.9050) or 077030C (Carbide) (0881.9050CAR) also 0881.8331.3

DELUXE PART NUMBER	MÜLLER PART NUMBER CROSS REFERENCE	PART DESCRIPTION
077014	0881.0123.4	Clincher Slide Assembly
077016	0881.0136.4	Clincher Mounting Bar
077017	0881.0140.3	Plate Insert
077018	0881.0141.3	Clincher Back Plate
077019	0881.0142.3	Clincher Front Plate
072012	0030.3488	Screw M6x1.0x20
077015	0881.0125.3	Clincher Point 1/2"
077029C	0881.0351.3	Clincher Slide Assembly, Carbide
G20520	0031.0557	Lock Washer Ribbed, M6

070830A (0305.0321) Also 0881.8334.3

DELUXE PART NUMBER	MÜLLER PART NUMBER CROSS REFERENCE	PART DESCRIPTION
070831		Clincher Back Plate, Bravo Plus
070832		Clincher Front Plate, Bravo Plus
070833	0881.4101.3	Clincher Slide, Carbide, Bravo Plus 5-5/16-135mm
070835		Clincher Mounting Bar, Bravo Plus
071006	0031.5105	Lock Washer, Ribbed M5
072020		Screw, M6x1.0x14, SHC
072021		Screw, M5x0.8x10, SHC Low Head
077015	0881.0125.3	Clincher Point 1/2"
077017B		Solid Clincher Plate Insert, Bravo & Primo (Optional) 2004 or Newer
G20520		Lock Washer Ribbed, M6

070850A (0881.8339) - Also 1550.0023

DELUXE PART NUMBER	MÜLLER PART NUMBER CROSS REFERENCE	PART DESCRIPTION
077017	0881.0140.3	Solid Clincher Plate Insert
070851	0881.3061.2	Clincher Back Plate, Medium Length
070852	1550.3060.2	Clincher Front Plate, Medium Length
070853	1550.3023.3	Clincher Slide Assy., Medium Length
070853C		Clincher Slide Assy., Carbide, 108mm Long
070855	1550.3033.4	Clincher Mounting Bar
070857		Screw, M6x1.0x8, FHM
072013	0030.9001	Screw M6x1.0x22
077015	0881.0125.3	Clincher Point 1/2"
077017B		Solid Clincher Plate Insert, Bravo & Primo (Optional) 2004 or Newer
G20520		Lock Washer Ribbed, 6mm

NOTES: